

Antistatic & ESD Chair -Comfort



Technical Specifications

ESD fabric

Spring-loaded mechanical controls for backrest and height adjustment

Lumbar support

European manufacturing, long-lasting

Wheels made of gray rubber, non-marking, shatterproof.

Assembly is the responsibility of the user.

Armrests and footrest rings are optional on all models.

Compliant with IEC 61340-5-1:2016



CH-6009: ESD Comfort (490-620 mm)

Seat Height Adjustment Range: 490-620 mm

Seat Dimensions: 440 x 460 mm

Back Measurements: 430 x 500 mm

CH-6011: ESD Comfort (580-760mm)

Seat Height Adjustment Range: 580-760mm

Seat Dimensions: 440 x 460 mm

Back Measurements: 430 x 500mm

CH-6010: ESD Comfort (610 – 860 mm) This model is fixed-base.

Seat Height Adjustment Range: 610- 860 mm.

Seat Dimensions: 440 x 460 mm

Back Measurements: 430 x 500 mm

Spare/Extra Products

CZ-KESD: Conductive Chair Arm

CH-KP: Foot Support

CZ-KCZP: Plastic Wheel

CZ-KCZ/K1: Rubber Wheel

CZ-KCZ/K5: Stainless Steel Wheel

CH-KCZ/K7: Conductive Fixed Foot

Compliant with IEC 61340-5-1:2016





CZ-KESD



CH-KP



CZ-KCZP



CH-KCZ/K5



CH-KCZ/K1



CH-KCZ/K7

Compliant with IEC 61340-5-1:2016

